

In@nominal overload [Arms]
Heavy: 200% x 3s + 150% x 30s [kW]
Light: 120% x 30s [kW]
Standard: 150% x 30s [kW]
Strong: 200% x 30s [kW]

OPDE _{plus} XS			
From 4 [A] to 12 [A]			
1,5	3,2	5,5	
1,8	3,8	6,5	
1,6	3,4	5,8	
1,3	2,7	4,7	

DIMENSIONS	
H - mm	276
L - mm	73
P/D - mm	168
Kg	2,5



TECHNICAL DATA SHEET OPDE _{plus} XS	TYPE	
	CM (CANbus-Multifeedback)	MM (MultiFieldbus-Multifeedback)
Supply voltage	230±10% Vac single-phase 3 x 230±10% Vac 3 x 400±10% Vac	
PC programming and device interfacing	Modbus RTU RS485	
Fieldbus	CANbus	PROFINET/EtherCAT
Digital/analog I/O	- n° 2 configurable digital output - n° 3 configurable digital input - S.T.O. safety function / additional 2 digital input - n°1 configurable analog input - Potentiometer Supply	
Sensor feedback	Resolver feedback + Multifeedback	

Permanent Magnet Synchronous motors (PMSM)	Closed loop with each of the fbk1 and fbk2 sensors	Synchronous Reluctance Motors (Synk & AsynRM)	Closed loop with each of fbk1 and fbk2
	Built in features for anisotropic motors (PMSM-IPM as MTPA and d-axis phasing @ standstill)		Optimized closed loop and sensorless control with flux linkage curves
	Sensorless (wide range) optimized for low speed high torque and high speed spindle motors		Motor control over a wide range of flux weakening
		PWM	~ Max 18 [KHz]*
Asynchronous molors (IM)	Closed loop FOC with each of the fbk1 and fbk2 sensors	Control loop bandwidth	Current loop: 1400~2000 [Hz] Max
	VF control, Modified VF control and optimized VF control with torque compensation		Speed loop: Max 200 [Hz]
	Sensorless (wide range) optimized for low speed high torque and high speed spindle motors		The max-min range depends of the overall computational effort
		* For switching frequency out of range, contact the technical office	

MAIN CONTROL FEATURES

- Update cycle internal loop: speed, current, positioning and speed task
- PLC task synchronized with the main PWM loop
- Flying Start for IM/PMSM/SynRM
- Two memory banks
- Mechanical System Identification
- Non linear electrical motor parameters identification

CERTIFICATIONS

Our **OPDE_{plus} XS** servo drive guarantees the best performance and simple use and can be used with many of the applications sought after on the market, in compliance with approved international Standards, such as EC (Europe), UL and CSA (USA and Canada)

